

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Trade name : Super Strip
Product code : 0424

1.2. Recommended use and restrictions on use

Recommended use : Floor strip products

1.3. Supplier

Synthetic Labs
24 Victory Lane
Dracut, MA, 01826
United States
T 800.255.4050 - F 978.957.5122
www.syntecpro.com

1.4. Emergency telephone number

Emergency number : Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation Category 1A Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : Causes severe skin burns and eye damage
Causes serious eye damage
Precautionary statements (GHS US) : Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Wear eye protection, protective gloves.
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Specific treatment (see supplemental first aid instruction on this label).
Wash contaminated clothing before reuse.
Store locked up.

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene Glycol Monobutyl Ether	CAS-No.: 111-76-2	20 – 30	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Monoethanolamine	CAS-No.: 141-43-5	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Corr. 1, H314 Eye Dam. 1, H318
Alcohols, Ehoxylated	CAS-No.: 68439-46-3	1 – 5	Acute Tox. 4 (Oral), H302

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Call a physician immediately. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Super Strip	
No additional information available	
Ethylene Glycol Monobutyl Ether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
Monoethanolamine (141-43-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	Eye & skin irr
USA - OSHA - Occupational Exposure Limits	
Local name	Ethanolamine
OSHA PEL (TWA) [1]	6 mg/m ³
OSHA PEL (TWA) [2]	3 ppm
Alcohols, Ehoxylated (68439-46-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	1 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [2]	1 ppm
OSHA PEL (STEL) [2]	5 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA [ppm]	5 ppm
NIOSH REL (Ceiling)	9 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: clear
Odor	: Fruity
Odor threshold	: No data available
pH	: 12.5
pH solution	: 11.5 – 12.5
Melting point	: Not applicable
Freezing point	: 32 °F
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.98 g/m ³
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethylene Glycol Monobutyl Ether (111-76-2)

LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	3 mg/l/4h

Monoethanolamine (141-43-5)

LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male / female, Experimental value, Dermal)
ATE US (oral)	1515 mg/kg body weight
ATE US (dermal)	1018 mg/kg body weight
ATE US (vapors)	11 mg/l/4h

Alcohols, Ehoxylated (68439-46-3)

LD50 oral rat	1378 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
ATE US (oral)	1378 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.
pH: 12.5

Ethylene Glycol Monobutyl Ether (111-76-2)

pH	No data available in the literature
----	-------------------------------------

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Monoethanolamine (141-43-5)	
pH	12.1 (100 g/l)

Serious eye damage/irritation : Causes serious eye damage.
pH: 12.5

Ethylene Glycol Monobutyl Ether (111-76-2)	
pH	No data available in the literature

Monoethanolamine (141-43-5)	
pH	12.1 (100 g/l)

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Ethylene Glycol Monobutyl Ether (111-76-2)	
Viscosity, kinematic	3.642 mm²/s (20 °C)

Monoethanolamine (141-43-5)	
Viscosity, kinematic	23.5 mm²/s (20 °C, EN ISO 3104: Capillary viscometer)

Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Ethylene Glycol Monobutyl Ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

Monoethanolamine (141-43-5)	
LC50 - Fish [1]	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	2.8 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Ethylene Glycol Monobutyl Ether (111-76-2)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Monoethanolamine (141-43-5)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
---------------------------------	-----------------------------------

Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
------------------------------	------------------------------------

ThOD	2.49 g O ₂ /g substance
------	------------------------------------

BOD (% of ThOD)	0.32
-----------------	------

Alcohols, Ehoxylated (68439-46-3)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

Ethylene Glycol Monobutyl Ether (111-76-2)

Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)
---	---

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

Monoethanolamine (141-43-5)

BCF - Other aquatic organisms [1]	2.3 – 9.2 (BCFWIN, Calculated value)
-----------------------------------	--------------------------------------

Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
---	---

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

Alcohols, Ehoxylated (68439-46-3)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

12.4. Mobility in soil

Ethylene Glycol Monobutyl Ether (111-76-2)

Surface tension	65.03 mN/m (20 °C, 2 g/l)
-----------------	---------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Highly mobile in soil.
----------------	------------------------

Monoethanolamine (141-43-5)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.16 (log Koc, Calculated value)
--	----------------------------------

Ecology - soil	Highly mobile in soil.
----------------	------------------------

12.5. Other adverse effects

No additional information available

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1760
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : 1760
UN-No. (IATA) : 1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : Not applicable

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1760
DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 154

IMDG

Special provision (IMDG) : 274
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP2, TP27
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG) : B
Stowage and handling (IMDG) : SW2
Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provision (IATA)	: A3
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Ethylene Glycol Monobutyl Ether	111-76-2	Present	Active	
Monoethanolamine	141-43-5	Present	Active	
Alcohols, Ehoxylated	68439-46-3	Present	Active	XU

15.2. International regulations

CANADA

Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Monoethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List)

Alcohols, Ehoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Component	State or local regulations
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Monoethanolamine(141-43-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

Super Strip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 1/8/2024

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.