

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Classic TLC
Product code : 1396

1.2. Recommended use and restrictions on use

Recommended use : Detergent, Carpet cleaning (liquids)

1.3. Supplier

Synthetic Labs
24 Victory Lane
Dracut, MA, 01826
United States
T 800.255.4050 - F 978.957.5122
www.syntecpro.com

1.4. Emergency telephone number

Emergency number : Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1A Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : Causes severe skin burns and eye damage
Causes serious eye damage
Precautionary statements (GHS US) : Do not breathe mist, spray, vapors.
Wash hands, forearms and face thoroughly after handling.
Wear eye protection, protective gloves.
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Specific treatment (see supplemental first aid instruction on this label).
Wash contaminated clothing before reuse.
Store locked up.

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Tetrasodium ethylenediaminetetraacetate	CAS-No.: 64-02-8	1 – 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Disodium Metasilicate	CAS-No.: 6834-92-0	1 – 5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 STOT SE 3, H335
Alcohols, Ehoxylated	CAS-No.: 68439-46-3	1 – 5	Acute Tox. 4 (Oral), H302
Ethylene Glycol Monobutyl Ether	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Classic TLC

No additional information available

Tetrasodium ethylenediaminetetraacetate (64-02-8)

No additional information available

Disodium Metasilicate (6834-92-0)

No additional information available

Alcohols, Ehoxylated (68439-46-3)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA [ppm]	1 ppm
---------------------	-------

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA) [2]	1 ppm
--------------------	-------

OSHA PEL (STEL) [2]	5 ppm
---------------------	-------

USA - NIOSH - Occupational Exposure Limits

NIOSH REL TWA [ppm]	5 ppm
---------------------	-------

NIOSH REL (Ceiling)	9 mg/m ³
---------------------	---------------------

Ethylene Glycol Monobutyl Ether (111-76-2)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA [ppm]	20 ppm
---------------------	--------

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: clear
Odor	: Fresh
Odor threshold	: No data available
pH	: 12.5
pH solution	: 11.5 – 12
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.03 g/m ³
Molecular mass	: 1.03 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Tetrasodium ethylenediaminetetraacetate (64-02-8)

LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)
ATE US (oral)	1780 mg/kg body weight

Disodium Metasilicate (6834-92-0)

LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1152 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

Alcohols, Ehoxyated (68439-46-3)

LD50 oral rat	1378 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
ATE US (oral)	1378 mg/kg body weight

Ethylene Glycol Monobutyl Ether (111-76-2)

LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (vapors)	3 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.
pH: 12.5

Tetrasodium ethylenediaminetetraacetate (64-02-8)

pH	11 (1 %)
----	----------

Disodium Metasilicate (6834-92-0)

pH	No data available in the literature
----	-------------------------------------

Ethylene Glycol Monobutyl Ether (111-76-2)

pH	No data available in the literature
----	-------------------------------------

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Causes serious eye damage.
pH: 12.5

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
pH	11 (1 %)

Disodium Metasilicate (6834-92-0)	
pH	No data available in the literature

Ethylene Glycol Monobutyl Ether (111-76-2)	
pH	No data available in the literature

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Disodium Metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Viscosity, kinematic	Not applicable (solid)

Disodium Metasilicate (6834-92-0)	
Viscosity, kinematic	Not applicable (solid)

Ethylene Glycol Monobutyl Ether (111-76-2)	
Viscosity, kinematic	3.642 mm ² /s (20 °C)

Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
LC50 - Fish [1]	121 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Soft water)
EC50 - Crustacea [1]	625 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Weight of evidence, Nominal concentration)

Disodium Metasilicate (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene Glycol Monobutyl Ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance

Disodium Metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Alcohols, Ehoxylated (68439-46-3)	
Persistence and degradability	Readily biodegradable in water.

Ethylene Glycol Monobutyl Ether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
BCF - Fish [1]	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Disodium Metasilicate (6834-92-0)	
Bioaccumulative potential	Not bioaccumulative.

Alcohols, Ehoxylated (68439-46-3)	
Bioaccumulative potential	No bioaccumulation data available.

Ethylene Glycol Monobutyl Ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Ecology - soil	Low potential for adsorption in soil.
Disodium Metasilicate (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
Ethylene Glycol Monobutyl Ether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Tetrasodium ethylenediaminetetraacetate	64-02-8	Present	Active	
Disodium Metasilicate	6834-92-0	Present	Active	
Alcohols, Ehoxylated	68439-46-3	Present	Active	XU
Ethylene Glycol Monobutyl Ether	111-76-2	Present	Active	

15.2. International regulations

CANADA

Tetrasodium ethylenediaminetetraacetate (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

Disodium Metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List)

Alcohols, Ehoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Classic TLC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Component	State or local regulations
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 1/8/2024

Hazard Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 0 Minimal Hazard - Materials that will not burn
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.