

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/9/2017 Revision date: 3/17/2017 Supersedes: 3/14/2017 Version: 2.0

SECTION 1: Identification	
1.1. Identification	
Product form Trade name Product code	: Mixture : Vision Tire Cleaner : 4711
1.2. Recommended use and restrictions o	n use
Recommended use	: Vehicle cleaning/vehicle care product, Rim cleaner (includes wheel cleaners)
1.3. Supplier	
Synthetic Labs 24 Victory Lane Dracut, MA, 01826 United States T 800.255.4050 - F 978.957.5122 www.syntecpro.com	
1.4. Emergency telephone number	
Emergency number	: Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053
SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mix	xture
GHS US classification	
Skin corrosion/irritation Category 1A Serious eye damage/eye irritation Category 1	Causes severe skin burns and eye damage
conous eye damage/eye imalion dalegory T	Causes serious eye damage
2.2. GHS Label elements, including preca	
2.2. GHS Label elements, including preca	
2.2. GHS Label elements, including preca GHS US labeling	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Tetrasodium ethylenediaminetetraacetate	CAS-No.: 64-02-8	1 – 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Ethylene Glycol Monobutyl Ether	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Disodium Metasilicate	CAS-No.: 6834-92-0	1 – 5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general First-aid measures after inhalation	 Call a physician immediately. Remove person to fresh air and keep comfortable for breathing. 	
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.	
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.	
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.	
4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	: Burns. : Serious damage to eyes. : Burns.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.	
5.2. Specific hazards arising from the chemical		
Hazardous decomposition products in case of fire	: Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective e	equipment and emergency procedures	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containr	nent and cleaning up	
Methods for cleaning up Other information	Take up liquid spill into absorbent material.Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.
	Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection		
8.1. Control parameters		
Vision Tire Cleaner		
No additional information available		
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
No additional information available		
Disodium Metasilicate (6834-92-0)		
No additional information available		
Ethylene Glycol Monobutyl Ether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm	
8.2. Appropriate engineering controls		
	Ensure good ventilation of the work station. Avoid release to the environment.	
8.3. Individual protection measures/Personal p	protective equipment	
Hand protection:		
Protective gloves		
Eye protection:		
Safety glasses		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respiratory equipment		
Personal protective equipment symbol(s):		



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties	
Physical state	: Liquid
Appearance	: Liquid.
Color	: Blue
Odor	: characteristic
Odor threshold	: No data available
рН	: 12.5
pH solution	: 11.5 – 12.5
Melting point	: Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Density Solubility	 No data available 1.04 g/m³ Soluble in water.
Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties	 No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified : Not classified	
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)		
ATE US (oral)	1780 mg/kg body weight	
Disodium Metasilicate (6834-92-0)		
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))	
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))	
ATE US (oral)	1152 mg/kg body weight	
ATE US (dust, mist)	1.5 mg/l/4h	
Ethylene Glycol Monobutyl Ether (111-76-2)		
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))	
ATE US (oral)	1414 mg/kg body weight	
ATE US (dermal)	1100 mg/kg body weight	
ATE US (vapors)	3 mg/l/4h	
Skin corrosion/irritation :	Causes severe skin burns. pH: 12.5	
Tetrasodium ethylenediaminetetraacetate (64	-02-8)	
рН	11 (1 %)	
Disodium Metasilicate (6834-92-0)	1	
рН	No data available in the literature	
Ethylene Glycol Monobutyl Ether (111-76-2)		
рН	No data available in the literature	
Serious eye damage/irritation :	Causes serious eye damage. pH: 12.5	
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
рН	11 (1 %)	
Disodium Metasilicate (6834-92-0)		
рН	No data available in the literature	
Ethylene Glycol Monobutyl Ether (111-76-2)		
рН	No data available in the literature	
Respiratory or skin sensitization :	Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure :	Not classified	
Disodium Metasilicate (6834-92-0)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	Not classified	
Aspiration hazard :	Not classified	
Viscosity, kinematic :	No data available	
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
Viscosity, kinematic	Not applicable (solid)	
Disodium Metasilicate (6834-92-0)		
Viscosity, kinematic	Not applicable (solid)	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Viscosity, kinematic	3.642 mm²/s (20 °C)	
Symptoms/effects after skin contact :	Burns.	
Symptoms/effects after eye contact	Serious damage to eyes.	
Symptoms/effects after ingestion	Burns.	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general :	Before neutralisation, the product may represent a danger to aquatic organisms.
Tetrasodium ethylenediaminetetraacetate (64-	02-8)
LC50 - Fish [1]	121 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Soft water)
EC50 - Crustacea [1]	625 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Weight of evidence, Nominal concentration)
Disodium Metasilicate (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
Ethylene Glycol Monobutyl Ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

.	
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance

12.2. Persistence and degradability

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)			
Chemical oxygen demand (COD)	0.54 - 0.58 g O ₂ /g substance		
Disodium Metasilicate (6834-92-0)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
Ethylene Glycol Monobutyl Ether (111-76-2)			
Persistence and degradability	Readily biodegradable in water.		
12.3. Bioaccumulative potential			
Tetrasodium ethylenediaminetetraacetate (64-02-8)			
BCF - Fish [1]	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)		
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
Disodium Metasilicate (6834-92-0)			
Bioaccumulative potential	Not bioaccumulative.		
Ethylene Glycol Monobutyl Ether (111-76-2)			
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
12.4. Mobility in soil			
Tetrasodium ethylenediaminetetraacetate (64	-02-8)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)		
Ecology - soil	Low potential for adsorption in soil.		
Disodium Metasilicate (6834-92-0)			
Surface tension	No data available in the literature		
Ecology - soil	Low potential for adsorption in soil.		
Ethylene Glycol Monobutyl Ether (111-76-2)			
Surface tension	65.03 mN/m (20 °C, 2 g/l)		

 Organic Carbon Normalized Adsorption Coefficient (Log Koc)
 0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

 Ecology - soil
 Highly mobile in soil.

12.5. Other adverse effects

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, I	March 26, 2012 / Rules and Regulations
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transport information	
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Not applicable Not applicable Not applicable Not applicable
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT)	: Not applicable
TDG Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG)	: Not applicable
IATA Transport hazard class(es) (IATA)	: Not applicable
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	 Not applicable Not applicable Not applicable Not applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT No data available	
TDG No data available	
IMDG No data available	
IATA No data available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Tetrasodium ethylenediaminetetraacetate	64-02-8	Present	Active	
Disodium Metasilicate	6834-92-0	Present	Active	
Ethylene Glycol Monobutyl Ether	111-76-2	Present	Active	

15.2. International regulations

CANADA

Tetrasodium ethylenediaminetetraacetate (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations	
Component	State or local regulations
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information			
according to Federal Register / Vo	I. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Revision date	: 3/17/2017		
Hazard Rating			
Health	: 2 Moderate Hazard - Temporary or minor injury may occur		
Flammability	: 0 Minimal Hazard - Materials that will not burn		
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.		
Safety Data Sheet (SDS), USA			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.