



Building & Facilities Maintenance Solutions



FLOOR STRIPPER

BreakThrough

Heavy Duty Floor Finish Stripper

CORE 3

Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 years.

Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.



Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.

FLOOR STRIPPERS

BreakThrough

Heavy Duty Stripper for Floor Finish

What is BreakThrough?

A professional strength, high speed no-rinse stripper that quickly emulsifies and breaks up today's toughest and long lasting finishes, by breaking the bond instead of dissolving it. Breakthrough will strip floors in less time and effort than conventional strippers due to its extremely aggressive nature, allowing cost savings by decreasing labor time. Will liquefy urethane fortified and acrylic finishes that most strippers won't. Lower odor allows for use in more places than traditional strippers.

Benefits:

- Strips quickly and easily.
- Removes long lasting finishes and semi-permanent finishes.
- Low foam allows for effortless automated cleanup.
- Lower odor formulation.
- Removes multiple layers in one shot.
- Rinse Free.
- No neutralization required.

Directions For Use

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area.

Wet floors may be slippery so prevent pedestrian traffic with signs or barricades.

Dilute with from 1 to 5 parts water when manually stripping.

Automatic scrubber solutions should be 1 part concentrate with 10 parts water.

Liberal apply to small area of approximately 100 square feet covering completely and to the baseboards.

Allow 3 to 5 minutes for chemical action, but do not allow to dry on the floor. Agitate with mop or machine scrub, then pick up solution using a wet vac or automatic scrubber.

Damp mop with clean water to remove residue.

Make sure to use proper protective clothing when applying this or any chemical. Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area.

Tech Specs:

Color.....Purple
 Fragrance.....Characteristic
 Form.....Liquid
 Phosphates.....None
 FlashPoint.....212F
 pH.....13.5
 Specific Gravity.....1.04
 Viscosity.....Thin
 Foam.....Moderate
 Biodegradable.....100%
 Shelf Life.....1 Year

Available Packages	
0429-275	275 Gallon Tote
0429-55	55 Gallon Plastic Drum
0429-30	30 Gallon Plastic Drum
0429-15	15 Gallon Plastic Drum
0429-5.25	2x2.5 Gallon Jugs
0429-5	5 Gallon Plastic Pail
0429-4	4 Gallon Case



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com