

Ultra 768

Concentrated Surface Protectant

Personal Attention Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Experience With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 years.

Technology Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.



Ultra Concentrate



Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.

PROTECTANTS

Ultra 768

ConcentratedTotal Vehicle Body Protectant

Contains Carnuaba For Added Performance

What is Ultra 768?

A premium drying agent and complete surface protectant in one product. Contains special polymers, builders, and siliconized carnauba that not only bead water from the surface during the drying cycle, but will provide protection to glass and surfaces after the vehicle has dried. Contains UV protectants for added protection.

Product Use Benefits:

- A complete surface protectant in one product.
- Provides clear coat protection and shine.
- Can be used as a single step product in most wash systems.
- Great for use in all water conditions.
- Contains Carnauba for added protection.

Use Recommendations:

- Tunnel or Conveyor Systems
- Automatic or Rollover Systems
- Manual Applicators

Available Packages		
4768-55	55 Gallon Plastic Drum	
4768-30	30 Gallon Plastic Drum	
4768-15	15 Gallon Plastic Drum	
4768-5.25	5 2x2.5 Gallon Jugs	
4768-5	5 Gallon Plastic Pail	

Tech Specs:

Color	Green
Fragrance	Melon
Form	Liquid
Phosphates	None
Flash Point	212°F
pH (Conc)	7

Specific Gravity	0.98
Viscosity	Thin
Foam	None
Shelf Life	1 Year

Synthetic Synthetic

Toll Free: 800-255-4050 24 Victory Lane, Dracut, MA 01826 www.syntecpro.com www.360carwashsolutions.com

Dilutions:

 Tunnel Wash System:
 1:400-1:800

 Automatic or Rollover:
 1:400-1:800

 Manual Drying Agent:
 1:400-1:800