



Food & Beverage Processing Cleaners

SURFACE CLEANING

Alka Chlor

Heavy Duty Chlorinated Cleaner

CORE 3

Core 3: Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Core 3: Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 years.

Core 3: Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.

Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.



SURFACE CLEANING

Alka Chlor

Heavy Duty Chlorinated Cleaner

What is Alka Chlor?

A chlorinated cleaner is designed for use in all food processing areas. This highly concentrated cleaner quickly and effectively penetrates and lifts animal fats, proteins, food residues, oil, grease and soap scum. Designed for use in foam generating equipment as well as soak and manual applications. This product is a heavy-duty, fully compounded cleaner that requires no chlorine additives, alkaline boosters or foaming detergents. Excellent for removal of carbonized, fatty, proteinaceous and blood soils from floors, walls, and food processing equipment. May be applied through foam-generating or pressure-washing equipment. Formulated to meet USDA standards for cleaning products.

Benefits:

- High foaming for easy application.
- Cleans and sanitizes in one quick step.
- Fortified with Sodium Hydroxide for removal of oils.
- Versatile enough to clean virtually any non aluminum surface.

Instructions:

Before use, read product label and Material Safety Data Sheet.

Cover or remove all food products from area to be cleaned. Remove gross accumulation of meat particles, soil and other waste materials from surfaces and equipment.

For cleaning kill floors and boning rooms: dilute 1:10- 1:20 with water. For processing equipment and conveyors: dilute 1:20-1:50

For floors and walls: dilute 1:30-1:50 Rinse thoroughly with potable water.

This product will remove many alkyd, lacquer and acrylic-base paints. Preliminary testing should be done before application to such surfaces is considered.

Do not use on aluminum, tin or zinc-plated surfaces. Pitting or surface deterioration may result.

Tech Specs:

Color.....Yellow
 Fragrance.....Chlorine
 Form.....Liquid
 Phosphates.....None
 FlashPoint.....212F
 pH.....13.5
 Specific Gravity.....1.06
 Viscosity.....Thin
 Foam.....High
 Biodegradable.....100%
 Shelf Life.....1 Year

Available Packages

6213-275	275 Gallon Tote
6213-55	55 Gallon Plastic Drum
6213-30	30 Gallon Plastic Drum
6213-15	15 Gallon Plastic Drum
6213-5.25	2x2.5 Gallon Jugs
6213-5	5 Gallon Plastic Pail
6213-4	4 Gallon Case



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com