

PARTS WASH

HydroJet

Low Foaming Parts Wash

CORE 3

Core 3: Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Core 3: Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 years.

Core 3: Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.

Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.



PARTS WASH

HydroJet

Low Foaming Aluminum Safe Parts Wash

What is HydroJet?

A new type of product which encourages oil and grease to "split" to the top of the containment vessel after use. HydroWash is specially formulated to clean metal parts without the aid of hazardous solvents or other hazardous materials and when used as directed, will remove heavy grease and grime without harming metal or painted parts. HydroWash has been specially formulated to be low foaming for use in industrial mechanical spray wash machines.

Benefits:

- Special heavy duty formula for deep penetration of grease and oils.
- Low foaming for use in rotary and mechanical spray wash machines.
- Will not harm metals or painted parts, or aluminum.
- Promotes splitting of oils for enhanced clean up.
- Contains special buffering ingredients to protect metals against corrosion.
- This product is 100% biodegradable for easy disposal.

Available Packages	
6372-275	275 Gallon Tote
6372-55	55 Gallon Plastic Drum
6372-30	30 Gallon Plastic Drum
6372-15	15 Gallon Plastic Drum
6372-5	5 Gallon Plastic Pail
6372-4	4 Gallon Case

Instructions:

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area.

Dilute with up to 20 parts water for cleaning armatures and generators.

Dilute with 20-40 parts water if using on aluminum parts. Use more concentrated for heavily soiled machine and automotive parts. Blow dry with compressed air.

Tech Specs:

Color.....Clear
 Fragrance.....Faint
 Form.....Liquid
 Phosphates.....None
 Flash Point.....212F
 pH.....9-9.5
 Specific Gravity.....1.01
 Viscosity.....Thin



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com