

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/9/2017 Revision date: 3/17/2017 Supersedes: 3/17/2017 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture Trade name Rhino Dry Product code 4781

1.2. Recommended use and restrictions on use

Recommended use : Rinse aid (includes drying aids)

1.3. Supplier

Synthetic Labs 24 Victory Lane Dracut, MA, 01826 **United States** T 800.255.4050 - F 978.957.5122 www.360carwashsolutions.com

1.4. Emergency telephone number

Emergency number : 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Serious eye damage/eye irritation Category 1 Aspiration hazard Category 1

Causes serious eye damage May be fatal if swallowed and enters airways

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) Danger

Hazard statements (GHS US) May be fatal if swallowed and enters airways

Causes serious eye damage

Precautionary statements (GHS US) : Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center or doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Do NOT induce vomiting.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Quaternary Ammonium Compounds	CAS-No.: Trade Secret	5 – 10	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318
Mineral Seal Oil	CAS-No.: 64742-46-7	5 – 10	Flam. Liq. 4, H227 Carc. 1B, H350
Ethylene Glycol Monobutyl Ether	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

3/17/2017 (Revision date) EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle

until all safety precautions have been read and understood. Wear personal protective equipment.

Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Rhino Dry

No additional information available

3/17/2017 (Revision date) EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mineral Seal Oil (64742-46-7)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m³	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (STEL) [1]	5 mg/m³	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA)	10 mg/m³	
Quaternary Ammonium Compounds (Trade Secret)		
No additional information available		
Ethylene Glycol Monobutyl Ether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
CGIH OEL TWA [ppm] 20 ppm		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

and protection:	
rotective gloves	
ye protection:	
afety glasses	
kin and body protection:	
Vear suitable protective clothing	
espiratory protection:	
n case of insufficient ventilation, wear suitable respiratory equipment	

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid. Color : red Odor : cherry

Odor threshold : No data available

pH : 7(7-8)pH solution : 7-8Melting point : Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point : No data available Boiling point : No data available Flash point No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Not applicable. Vapor pressure No data available No data available Relative vapor density at 20°C Relative density No data available Density 0.98 a/m³

Solubility No data available : No data available Partition coefficient n-octanol/water (Log Pow) · No data available Auto-ignition temperature : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties No data available No data available Oxidizing properties

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Mineral Seal Oil (64742-46-7)

LD50 oral rat > 5000 mg/kg

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mineral Seal Oil (64742-46-7)		
LD50 dermal rabbit	> 2000 mg/kg	
Quaternary Ammonium Compounds (Trade S	Secret)	
ATE US (oral)	500 mg/kg body weight	
Ethylene Glycol Monobutyl Ether (111-76-2)		
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))	
ATE US (oral)	1414 mg/kg body weight	
ATE US (vapors)	3 mg/l/4h	
Skin corrosion/irritation :	Not classified pH: 7 (7 – 8)	
Quaternary Ammonium Compounds (Trade S	Secret)	
рН	6 – 9	
Ethylene Glycol Monobutyl Ether (111-76-2)		
рН	No data available in the literature	
Serious eye damage/irritation :	Causes serious eye damage. pH: 7 (7 – 8)	
Quaternary Ammonium Compounds (Trade S	Secret)	
рН	6 – 9	
Ethylene Glycol Monobutyl Ether (111-76-2)		
рН	No data available in the literature	
Respiratory or skin sensitization :	Not classified	
3	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
STOT-repeated exposure :	Not classified	
Aspiration hazard : /iscosity, kinematic :	May be fatal if swallowed and enters airways. No data available	
Mineral Seal Oil (64742-46-7)		
Viscosity, kinematic	> 20.5 mm²/s (40 °C, Niet experimenteel bepaald; afgeleid van de indeling)	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Viscosity, kinematic	3.642 mm²/s (20 °C)	
Symptoms/effects after skin contact Symptoms/effects after eye contact	Irritation. Serious damage to eyes.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Ethylene Glycol Monobutyl Ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Ethylene Glycol Monobutyl Ether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

Ethylene Glycol Monobutyl Ether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

Ethylene Glycol Monobutyl Ether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

3/17/2017 (Revision date) EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Mineral Seal Oil	64742-46-7	Present	Active	
Quaternary Ammonium Compounds	Trade Secret	Present	Active	XU
Ethylene Glycol Monobutyl Ether	111-76-2	Present	Active	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Mineral Seal Oil (64742-46-7)

Listed on the Canadian DSL (Domestic Substances List)

Quaternary Ammonium Compounds (Trade Secret)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Component	State or local regulations
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 3/17/2017

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

3/17/2017 (Revision date) EN (English US) 9/9