

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Ultra 131
Product code : 4791

1.2. Recommended use and restrictions on use

Recommended use : Floor strip products

1.3. Supplier

Synthetic Labs
24 Victory Lane
Dracut, MA, 01826
United States
T 800.255.4050 - F 978.957.5122
www.syntecpro.com

1.4. Emergency telephone number

Emergency number : Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : Causes severe skin burns and eye damage
Causes serious eye damage
Precautionary statements (GHS US) : Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Specific treatment (see supplemental first aid instruction on this label).
Wash contaminated clothing before reuse.
Store locked up.

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---------------------------------|--------------------|---------|--|
| Monoethanolamine | CAS-No.: 141-43-5 | 15 – 20 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332 Skin Corr. 1, H314 Eye Dam. 1, H318 |
| Ethylene Glycol Monobutyl Ether | CAS-No.: 111-76-2 | 10 – 15 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a physician immediately. Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Wash skin with plenty of water. Take off contaminated clothing. Remove/Take off immediately all contaminated clothing. Call a physician immediately. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a physician immediately. |
| First-aid measures after ingestion | : Rinse mouth. Do not induce vomiting. Call a physician immediately. Call a poison center/doctor/physician if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|---------------------------|
| Symptoms/effects after skin contact | : Burns. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|---|---------------------|
| Ultra 131 | |
| No additional information available | |
| Ethylene Glycol Monobutyl Ether (111-76-2) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 20 ppm |
| Monoethanolamine (141-43-5) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Ethanolamine |
| ACGIH OEL TWA [ppm] | 3 ppm |
| ACGIH OEL STEL [ppm] | 6 ppm |
| Remark (ACGIH) | Eye & skin irr |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Ethanolamine |
| OSHA PEL (TWA) [1] | 6 mg/m ³ |
| OSHA PEL (TWA) [2] | 3 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

| |
|--|
| Hand protection: |
| Protective gloves |
| Eye protection: |
| Safety glasses |
| Skin and body protection: |
| Wear suitable protective clothing |
| Respiratory protection: |
| In case of insufficient ventilation, wear suitable respiratory equipment |

Personal protective equipment symbol(s):



Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-------------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Color | : Yellow |
| Odor | : Fresh |
| Odor threshold | : No data available |
| pH | : 13 |
| Melting point | : Not applicable |
| Freezing point | : 32 °F |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20°C | : No data available |
| Relative density | : No data available |
| Density | : 0.98 g/m ³ |
| Solubility | : Soluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|--|
| LD50 oral rat | 1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s)) |
| LD50 oral | 1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rat | > 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 1414 mg/kg body weight |
| ATE US (vapors) | 3 mg/l/4h |

| Monoethanolamine (141-43-5) | |
|-----------------------------|---|
| LD50 oral rat | 1089 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | 2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 1.3 mg/l air (6 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 1089 mg/kg body weight |
| ATE US (dermal) | 2504 mg/kg body weight |
| ATE US (vapors) | 11 mg/l/4h |

Skin corrosion/irritation : Causes severe skin burns.
pH: 13

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|-------------------------------------|
| pH | No data available in the literature |

| Monoethanolamine (141-43-5) | |
|-----------------------------|-------------|
| pH | 12.1 (10 %) |

Serious eye damage/irritation : Causes serious eye damage.
pH: 13

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|-------------------------------------|
| pH | No data available in the literature |

| Monoethanolamine (141-43-5) | |
|-----------------------------|-------------|
| pH | 12.1 (10 %) |

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|------------------------|---------------------|
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : No data available |

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|--|
| Viscosity, kinematic | 3.642 mm ² /s (20 °C) |
| Monoethanolamine (141-43-5) | |
| Viscosity, kinematic | 23.5 mm ² /s (20 °C, EN ISO 3104: Capillary viscometer) |
| Symptoms/effects after skin contact | : Burns. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|---|
| Ecology - general | : Before neutralisation, the product may represent a danger to aquatic organisms. |
|-------------------|---|

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|--|
| LC50 - Fish [1] | 1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal) |
| EC50 - Crustacea [1] | 1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 algae | 1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) |
| Monoethanolamine (141-43-5) | |
| LC50 - Fish [1] | 349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP) |
| EC50 - Crustacea [1] | 27 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration) |
| ErC50 algae | 2.8 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

12.2. Persistence and degradability

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|--|--|
| Persistence and degradability | Readily biodegradable in water. |
| Monoethanolamine (141-43-5) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.8 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.34 g O ₂ /g substance |
| ThOD | 2.49 g O ₂ /g substance |

12.3. Bioaccumulative potential

| Ethylene Glycol Monobutyl Ether (111-76-2) | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 0.81 (Experimental value, BASF test, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Monoethanolamine (141-43-5)

| | |
|---|---|
| Partition coefficient n-octanol/water (Log Pow) | -2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential | Not bioaccumulative. |

12.4. Mobility in soil

Ethylene Glycol Monobutyl Ether (111-76-2)

| | |
|--|--|
| Surface tension | 65.03 mN/m (20 °C, 2 g/l) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

Monoethanolamine (141-43-5)

| | |
|--|-------------------------------------|
| Surface tension | No data available in the literature |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1.2 (log Koc, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1760
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : 1760
UN-No. (IATA) : 1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 8

Hazard labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8

Hazard labels (IATA) : 8



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : Not applicable
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1760

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: t_r is the maximum mean bulk temperature during transport, t_f is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (t_f) and the maximum mean bulk temperature during transportation (t_r) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d_{15} and d_{50} are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 154 |
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 202 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 242 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 1 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 30 L |
| DOT Vessel Stowage Location | : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. |
| DOT Vessel Stowage Other | : 40 - Stow "clear of living quarters" |

TDG

| | |
|---------------------------------------|-------|
| Emergency Response Guide (ERG) Number | : 154 |
|---------------------------------------|-------|

IMDG

| | |
|------------------------------------|--|
| Special provision (IMDG) | : 274 |
| Packing instructions (IMDG) | : P001 |
| IBC packing instructions (IMDG) | : IBC02 |
| Tank instructions (IMDG) | : T11 |
| Tank special provisions (IMDG) | : TP2, TP27 |
| EmS-No. (Fire) | : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE |
| EmS-No. (Spillage) | : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES |
| Stowage category (IMDG) | : B |
| Stowage and handling (IMDG) | : SW2 |
| Properties and observations (IMDG) | : Causes burns to skin, eyes and mucous membranes. |

IATA

| | |
|--|--------|
| PCA Excepted quantities (IATA) | : E2 |
| PCA Limited quantities (IATA) | : Y840 |
| PCA limited quantity max net quantity (IATA) | : 0.5L |
| PCA packing instructions (IATA) | : 851 |
| PCA max net quantity (IATA) | : 1L |
| CAO packing instructions (IATA) | : 855 |
| CAO max net quantity (IATA) | : 30L |
| Special provision (IATA) | : A3 |
| ERG code (IATA) | : 8L |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

| Name | CAS-No. | Listing | Commercial status | Flags |
|---------------------------------|----------|---------|-------------------|-------|
| Ethylene Glycol Monobutyl Ether | 111-76-2 | Present | Active | |
| Monoethanolamine | 141-43-5 | Present | Active | |

Ultra 131

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Monoethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

| Component | State or local regulations |
|---|--|
| Ethylene Glycol Monobutyl Ether(111-76-2) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Monoethanolamine(141-43-5) | U.S. - New Jersey - Right to Know Hazardous Substance List |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 1/8/2024

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.